



CONCRETE RESURFACER: A-500
COLOR:GRAY

Recommended Applications

Industrial
Commercial
Residential

Product Description: A-500

A-500 Micro Finish was designed to resurface and patch concrete. The A-500 can also be used to resurface and/or create beautiful countertop finishes. Micro Finish must be applied as a feather edge coating that can be applied at 1/64 inch. Can be applied by squeegee or trowel.

Surface Preparation: A-500

The concrete surface must be clean and the pores of the concrete must be opened. This can be achieved by a blast track, acid wash or power washing. Do not apply product over hard trowel or sealed surfaces.

Mixing Procedures: A-500

This product only requires water. Different amounts of water will need to be added for different applications. If a thin overlay (1/64 inch) is the desired thickness, add approximately 6 quarts of water to each 35 lb bag or bucket. See application procedures.

Application of Concrete Resurfacer A-500

The surface must be pre-dampened with A-300 Concrete Bonder Admix before application of A-500. Apply A-500 by using a squeegee, broom, trowel, or sprayer apparatus. Coverage will be approximately 280 to 700 square feet per bag depending upon the existing concrete conditions. Surface must be sealed with one for the Americrete sealers.

Caution: A-500

Always wear protective clothing, eye protection, and filtered masks when mixing or using Americrete products. Wash hands after using products. If there is eye contact, flush with water, and consult a physician if irritation continues. Keep away from children. This material has no ingredients which are required to be listed by OSHA per 29 CFF 1910.1200.

Warranty: A-500

Americrete Inc., Americrete LLC. warrants Concrete Resurfacer A-500 to have been blended to the highest quality. Americrete does not give a warranty to any persons, company, or private individuals that have not attended an Americrete training class, and that has been approved to be a certified applicator of Americrete products. This warranty is a limited warranty, and only replacement of material (product) will be granted only if the product has been applied to manufacturers specifications, and over a sound concrete or plywood substrate. This would be the limit of liability to Americrete Inc. and Americrete LLC. No warranty for cracking.

AMERICRETE LLC.
SANTA FE SPRINGS, CA 90670
(800) 775-8880

Net Wt. 35 lbs.