



LIFE PAINT

PRODUCT SPECIFICATIONS



ROOF COATING

Stretch-Guard Level Lite

SGLL-30

Recommended Applications:

Industrial Commercial Residential

Packaging:

30 lb bag, gray

Product Description:

Stretch-Guard Level Lite is a light weight cement used for filling in areas where ponding water accumulates on a flat, or slightly pitched, roof. It is a dry, single component blend of silica, resins, aggregates, and cements.

Surface Preparation:

The surface must be clean and clean of oil, dust, mildew, silicones, and efflorescence. Leaks must be properly sealed by means of a waterproof product, and typically, a seam tape.

Priming:

A primer may be necessary depending on the type of existing roof membrane (acrylic, urethane foam, silicone, TPO, Hypalon, etc.), coating, and/or condition of the surface that the SGLL-30 will be applied to. If you are unsure whether or not to use a primer, please call Life Paint at (562) 944-6391 and ask for technical assistance.

Mixing Procedures:

This product only requires water. Mix approximately 4 to 4.25 quarts of water to each 30 lb bag in a clean bucket. *Add the water to the bucket before adding the SGLL-30.*

Application of SGLL-30 Level Lite:

Apply SGLL-30 by using a trowel. Pour product onto the surface to be repaired. Spread evenly creating a level surface or a slight pitch to move water towards the desired direction.

Coverage:

12 Square feet per 1/2 inch depth.

Caution:

Always wear protective clothing, eye protection, and filtered masks when mixing or using SGLL-30. Wash hands after using products. If there is eye contact, flush with water, and consult a physician if irritation continues. Keep away from children. This material has no ingredients which are required to be listed by OSHA per 29 CFF 1910.1200.

Warranty:

LIFE PAINT CO. warrants LEVEL LITE SGLL-30 to have been blended to the highest quality. LIFE PAINT CO. does not give a warranty to any persons, company, or private individuals that have not attended a LIFE PAINT CO. training class, and that has been approved to be a certified applicator of LIFE PAINT CO. products. This warranty is a limited warranty, and only replacement of material (product) will be granted only if the product has been applied to manufacturers specifications, and over a sound concrete or cementitious substrate. This would be the limit of liability to LIFE PAINT CO.