



LIFE PAINT

PRODUCT SPECIFICATIONS



COLORING- TOP COATS & SEALERS

20 SERIES PENETRATING SEMI-TRANSPARENT CONCRETE STAIN

Description: Life Deck 20 Series Transparent Concrete Stain creates a unique variation of color over bare concrete. It creates a beautiful multi-hue appearance.

Use: When applied in accordance to label instructions, Life Deck will penetrate into the concrete surface leaving no film that will chip or peel. Use over properly prepared masonry, concrete, and LifeDeck Texture Concrete Overlay surfaces. The bare concrete surface must be porous and profiled to resemble fine or medium sandpaper.

Advantages:

- * Penetrating
- * Natural Look
- * Water Clean-Up

Finish: None

Package Size:

Gallons, Quarts

Colors:

- | | |
|----------------|-------------------|
| -62 Gray Slate | -65 Sedona Red |
| -63 Sandstone | -67 Sienna |
| -64 Umber | -68 Green Slate |
| -71 Black | -72 Mediterranean |

SURFACE PREPARATION: Proper surface preparation is essential for penetration of the stain. Surface must be clean and porous prior to staining.

Concrete, concrete decks, floors and walk ways:

New concrete must age for a minimum of 30 days. Cool temperatures and high humidity may require a longer cure time. Remove all grease, oil and wax with T.S.P. Solution. (One pound of T. S. P. to 1 gallon of water.) Scrub with stiff broom until surface is thoroughly clean. Rinse thoroughly with clear water then etch (see etching instructions). A properly etched concrete surface should resemble the texture of fine or medium sandpaper. Let dry thoroughly before applying stain.

Etching Instructions: For acid etching, use 1 part 10% muriatic acid to 4 parts water. Wear appropriate eye, skin and apparel protection when applying etching solution. Protect plants and other surface from any splashing. Work etching solution into surface with a stiff bristle broom. Allow muriatic solution to remain on surface approximately 15 minutes. After etching, neutralize acid with baking soda or soda ash. Rinse thoroughly with water and allow to dry. Sweep and/or vacuum all residue left from etching process.

Aged, Uncoated Concrete: Remove all dirt, grease and oil with a cleaner or de-greaser. Follow manufacturer's directions. Rinse thoroughly with water and allow to dry. Smooth concrete surfaces must be properly etched. Follow etching instructions.

Painted, Stained or Sealed Concrete:

Do not apply over previously painted, stained (except as noted in "DRY TIME") or sealed concrete.

Application: Allow concrete surfaces to dry before applying stain. When working with more than one container of the same product, intermix to ensure color uniformity. Stir stain before and occasionally during application. Use product when temperature is between 50°F-80°F. Use caution when applying the transparent penetrating stain to a very hot surface. Premature drying of the stain prevents optimum penetration and the development of its transparent character. Lightly dampen very hot surfaces to cool them down before applying stain. (Do not puddle or flood water onto the surface).

Apply the stain with a conventional garden sprayer, using a push broom to spread it over the surface to be stained. To achieve a beautiful multi-hue appearance, use multiple coats of the stain/mixture thinned as desired with water (from 1 quart of water to 1 gallon of stain or up to 4 gallons of water to 1 gallon of stain). Variations of stain concentration and multiple coats of the stain mixture will produce attractive shading and interesting ranges of color intensities. For very dark, deep accents, use the stain full strength. Stain must be sealed with one of these choices:

- Water Based- 2110/2112 2K Urethane, 2114/2116 Urethane or 4001/4002 Acrylic Urethane.
- Solvent Based- 2009 Poly Aspartic, 2003 CRU Chemical Resistance 2K Urethane, LD7530 Urethane, 2008 Stone Glaze, or LD31-96 100% Solids Clear Epoxy System.

Coverage: Apply at a spread rate of 200-400 square feet per gallon. If the concrete is broken into sections, apply stain in sections for ease of application.

Dry Time: Subsequent coats of "20" Series stain can be applied at any time after 1st application if a darker color is desired. Allow the product to dry 24 hours before top coating and sealing with your choice of Life Deck Clear Coatings (see application instructions). Make sure shoes are clean or wear baggies around shoes to prevent footprints before finishing with clear coating. (Caution, baggies may be slippery).

Cool temperatures and high humidity may require a longer cure time.

Thinning: Water may be added to lighten color, from 1 quart to 4 gallons of water per gallon of stain.

Clean-up: Warm soapy water.

20 SERIES PENETRATING SEMI-TRANSPARENT CONCRETE STAIN

Important: Attempting to apply the first coat with a brush or roller may result in lap marks.

Horizontal surfaces may be subject to premature wear, therefore periodic touch-ups may be necessary. Retain any left over stain for this purpose.

Caution: Do not take internally. Close container after each use. KEEP OUT OF REACH OF CHILDREN.
NON-PHOTOCHEMICALLY REACTIVE
(Less than 4%)

Special Notes: Uneven cement, colorings, textures, and porosities, develop varying hues of color.

MILDEW: DO NOT PAINT OVER MILDEW. Mildew is a fungus, brown, black, grey or even white in color, and will rapidly grow through any coating applied over it.

Technical Information

Type: Acrylic
Diluent: Water

Flash Point: >400°F
Material V.O.C.: <25 gram per liter
(low solids coating)