LIFE™

Product Specifications

3001 Gloss/ 3002 Satin 100% Acrylic Urethane Top Coat

Description: Life's Acrylic Urethane is a crystal clear finish that is super durable and will not yellow. This premium quality product is formulated with ingredients that screen out the destructive ultra violet rays of the sun, one of the principal causes of deterioration and loss of gloss on any varnish film

Use: Life's Acrylic Urethane is designed to add a gloss finish and chemical resistance to wood and previously coated surfaces.

Recommended Surfaces:
Interior-Exterior Wood Surfaces

Advantages
- ✔ Chemical resistant
- ✔ Water Based
- ✔ UV Resistant
- ✔ Easy to use

Finish: 3001 Gloss, 3002 Satin

Package Size: Quarts, Gallons & 5 Gallons

Surface Preparation: All surfaces must be free of dirt, oil, soot, wax or other contaminants. On exterior surfaces, a thorough washing with a T.S.P. solution is recommended. Rinse clean with water. If sanded, remove all traces of sanding dust. Remove all cracked or alligator finishes.

Renewing Old Finish: Thoroughly clean surface to remove all traces of dirt, wax, oil or grease. Sand lightly with fine sandpaper and remove all dust. Apply one or two thin coats, sanding lightly between coats.

New Wood/Bare Wood: Sand wood with successively finer grades of sandpaper until a smooth surface is obtained. Remove all dust and dirt from the surface and make sure to clean the cracks in the wood. After the first **thin** coat has dried, sand lightly with fine grade sandpaper. Remove all dust and apply a second coat.

Mildew: DO NOT PAINT OVER MILDEW. Mildew is a fungus, brown, black, grey or even white in color, and will rapidly grow through any coating applied over it. A solution of 50% household bleach and 50% water will kill the mildew. Rinse thoroughly. See precautions on bleach label for handling before using.

Application: Brush, roll or spray. DO NOT SHAKE. Shaking will cause air bubbles. Stir gently and thoroughly before application. This product appears milky when wet, but dries rapidly to a beautiful clear coating.

3001 Gloss/3002 Satin — 100% Acrylic Urethane Top Coat

IMPORTANT: Do not apply late in day or when dew, rain, fog or mist is likely, since moisture will damage the fresh paint film. Apply at temperatures above 50 degrees F. Do not apply if temperatures below 45 degrees are expected within 24 hours. Cold weather or excess humidity or sudden temperature drop will greatly affect any finish at the time of application. Dampness can dull the gloss. Do not paint in direct sun. Use a clean brush or roller.

Coverage: Up to 400 sq. ft. per gallon on smoother surfaces, up to 150 to 300 sq. ft. per gallon on rough textured or porous surfaces. For best durability, we recommend at least two coats.

Drying Time: Dries within 30 minutes and can be recoated in 4 hours. Ready for use 12 hours. Drying time will vary with weather conditions, air circulation and temperature.

Thinning: If necessary, a small amount of water. Do not overthin.

Clean Up: Clean all equipment and tools immediately after use with warm soapy water.

Technical Information

Type:	100% Acrylic	**Viscosity:**	60 KREBS units at 77°F
Diluent:	Water	**Flash Point:**	200°F
Solids Content:	31-33% by weight 32-34% by volume	**Maximum V.O.C.:**	50 grams per liter

This product contains chemicals known to the State of California to cause cancer, birth defects and reproductive harm. The maximum V.O.C. of this product does not exceed 250 grams/liter. WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. KEEP FROM FREEZING.