

Safety Data Sheet

LD2003 – PART B - RESIN

Revision date: 2015/11/12

1. Identification

Product identifier used on the label

LD2003 - PART B - RESIN

Recommended use of the chemical and restriction on use:

Industrial Maintenance Coating, Waterproofing/Concrete Masonry Sealer

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

Life Paint Company

12927 Sunshine Avenue

Santa Fe Springs, CA 90670

562-944-6391

Emergency telephone number

CHEMTREC: 1-800-424-9300

Other means of identification

Chemical family: Modified Polyester Resin Solution

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200

Classification of the product

Flammable liquid, Category 3

Reproductive toxicity, Category 1B

Label Elements

Pictogram:



Signal Word: Danger

Hazard Statement:

Flammable

Safety Data Sheet

LD2003 – PART B - RESIN

Revision date: 2015/11/12

Harmful if inhaled.
Toxic if inhaled.
May cause respiratory irritation.
May damage fertility or the unborn child.
May cause respiratory irritation.
Causes serious eye irritation
May cause drowsiness or dizziness

Precautionary Statements (Prevention):

Wear eye/face protection.
Wear protective gloves.
Use only outdoors or in a well-ventilated area.
Do not breathe dust/gas/mist/vapors.
Avoid release to the environment.
Contaminated work clothing should not be allowed out of the workplace.
Wash with plenty of water and soap thoroughly after handling
Keep away from heat, hot surfaces, open flames, sparks – No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical, lighting, ventilating equipment
Use only non-sparking tools
Take Precautionary measures against static discharge

Precautionary Statements (Response):

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF ON SKIN (or hair): Wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Take off contaminated clothing and wash before reuse.
In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂) for extinction

Precautionary Statements (Storage):

Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Keep cool

Precautionary Statements (Disposal):

Dispose of contents/container to hazardous or special waste collection point.

Hazards not otherwise classified

No specific dangers known

Supplemental information:

Potential Health Effects:

Due to the presence of the solvent: Prolonged or repeated skin contact may cause defatting resulting in drying, redness and rash. Contains high molecular weight polymer(s). Effects due to processing releases: Irritating to eyes, respiratory system and skin. Prolonged or repeated exposure may cause: headache, drowsiness, nausea, weakness, (severity of effects depends on extent of exposure). Use with local exhaust ventilation. Wear protective clothing. Wear full face shield if splashing hazard exists.

3. Composition / Information on Ingredients

Safety Data Sheet

LD2003 – PART B - RESIN

Revision date: 2015/11/12

Components	CAS Number	Concentration (Weight)
Polyester Resin Solution	Proprietary	35-65 %
Propylene Glycol Monomethyl Ether Acetate	108-65-6	20-45 %
Benzene, 1-Chloro-4(trifluoromethyl)	98-56-6	10-25 %
Methyl Acetate	79-20-9	10-25 %
Proprietary	Proprietary	< 20 %

4. First-Aid Measures

Description of first aid measures

General advice:

Immediately remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

If on skin:

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Seek medical attention.

If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

Most important symptoms and effects, both acute and delayed:

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote, administer corticosteroid dose aerosol to prevent pulmonary odema.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media: Preferable: Alcohol resistant foam. Water spray, CO2
Unsuitable extinguishing media: Solid water jet ineffective as extinguishing medium

Special hazards arising from the substance or mixture

Hazards during fire-fighting: harmful vapors

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Safety Data Sheet

LD2003 – PART B - RESIN

Revision date: 2015/11/12

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

Fire Hazard:

Highly flammable. Gas/vapour flammable with air within explosion limits. INDIRECT FIRE HAZARD. May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard. Reactions involving a fire hazard: see "Reactivity Hazard"

Explosion Hazard:

DIRECT EXPLOSION HAZARD. Gas/vapour explosive with air within explosion limits. INDIRECT EXPLOSION HAZARD. Heat may cause pressure rise in tanks/drums: explosion risk. May be ignited by sparks. Reactions with explosion hazards: see "Reactivity Hazard".

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing.

Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and Storage

General information on handling:

Do not taste or swallow.

Do not get in eyes, on skin, or on clothing.

Do not breathe vapor or mist.

Keep away from heat, sparks and flames.

No smoking.

Keep container closed.

Use only with adequate ventilation.

Wash thoroughly after handling.

Check that all equipment is properly grounded and installed to satisfy electrical classification requirements.

Container hazardous when empty.

Follow label warnings even after container is emptied.

RESIDUAL VAPORS MAY EXPLODE ON IGNITION.

DO NOT CUT, DRILL, GRIND, OR WELD ON OR NEAR THIS CONTAINER.

Improper disposal or reuse of this container may be dangerous and/or illegal.

Emptied container retains vapor and product residue.

Safety Data Sheet

LD2003 – PART B - RESIN

Revision date: 2015/11/12

Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place away from heat sources, direct sunlight.

Storage stability:
May react with oxygen to form peroxides

Storage Incompatibility – General
Store separate from:
Strong acids, Strong oxidizing agents, Strong Bases, Reducing Agents.

Storage Temperature: 15 – 20 C

Storage Area:
Store in a cool area. Keep out of direct sunlight. Store in a dry area. Store in a dark area. Ventilation at floor level. Fireproof storeroom. Provide for an automatic sprinkler system. Provide for a tub to collect spills. Provide the tank with earthing. Meet the legal requirements.

Special rules on packaging:
SPECIAL REQUIREMENTS: closing with pressure relief valve. clean. opaque. correctly labelled. meet the legal requirements. Secure fragile packaging in solid containers.

Packaging materials:
SUITABLE MATERIAL: steel. stainless steel. carbon steel. aluminum. iron. copper. nickel. bronze. glass.
MATERIAL TO AVOID: synthetic material

8. Exposure Controls/Personal Protection

Engineering Measures

Provide readily accessible eye wash stations and safety showers.
Provide natural or explosion-proof ventilation adequate to ensure concentrations are kept below exposure limits

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) organic vapor/particulate respirator. Do not exceed the maximum use concentration for the respirator face piece/cartridge combination. For emergency or non-routine, high exposure situations, use a NIOSH-certified full face piece pressure demand self-contained breathing apparatus (SCBA) or a full face piece pressure demand supplied-air respirator (SAR) with escape provisions.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is required additionally to the stated personal protection equipment. Avoid inhalation of mists. Contact with eyes and skin must be avoided.

Safety Data Sheet

LD2003 – PART B - RESIN

Revision date: 2015/11/12

Occupational Exposure limit(s)

2-Propanol, 1-methoxy-, acetate (108-65-6)	Time Weighted Average (TWA):	50 ppm (listed)
Methyl acetate	Time Weighted Average (TWA):	200 ppm (listed)

9. Physical and Chemical Properties

Form:	liquid
Odor:	Solvent, sweet
Color:	Clear-Amber, Cloudy
pH value:	N/A
Melting point:	No data available
Boiling point:	56 °C
Flash point:	-13.0 °C Tag Closed Cup
Flammability:	Highly flammable
Lower explosion limit:	Not applicable
Upper explosion limit:	Not applicable
Vapor pressure:	< 0.03 hPa at 20 °C
Density:	1.15 g/cm ³ at 20 °C
Viscosity, Dynamic	500-1000 CPS
Solubility in Water	Hydrolyzes
Evaporation rate:	Not determined
Volatile Organic Compounds:	< 100 g/l (per AQMD)

10. Stability and Reactivity

Corrosion to metals:
Corrosion effect on metals are not anticipated

Chemical Stability:
Stable under normal conditions.

Conditions to avoid:
Avoid moisture. Avoid sources of ignition.

Materials to avoid:
Strong acids
Strong oxidizing agents
Strong bases
Reducing agents
May react with oxygen to form peroxides

Hazardous decomposition products:
Thermal decomposition giving flammable and toxic products:
Carbon oxides
Hazardous organic compounds

Safety Data Sheet

LD2003 – PART B - RESIN

Revision date: 2015/11/12

11. Toxicological information

Data on this material and/or its components are summarized below.

Inhalation:
4 h Acute toxicity estimate > 40 mg/l. (vapor)

Data for 2-Propanol, 1-methoxy-, acetate (108-65-6)

Acute toxicity

Oral:
Practically nontoxic. (Rat) LD50 = 6,190 mg/kg.

Dermal:
Practically nontoxic. (Rabbit) LD0 > 5,000 mg/kg.

Skin Irritation:
Not irritating. (Rabbit) Irritation Index: 0/8. (4 h)

Eye Irritation:
Causes mild eye irritation. (Rabbit)

Skin Sensitization:
Not a sensitizer. Guinea pig maximization test. (Guinea pig) No skin allergy was observed

Repeated dose toxicity

Repeated inhalation administration to rat, mouse / affected organ(s): nasal tissues

Subacute oral administration to rat / affected organ(s): adrenal gland / signs: changes in body weight, changes in organ weights

Genotoxicity

Assessment in Vitro:
No genetic changes were observed in laboratory tests using: bacteria, animal cells

Developmental toxicity

Exposure during pregnancy. Inhalation (rat) / No birth defects were observed.

Reproductive effects

Reproductive/Developmental Effects Screening Assay. Oral (rat) / No toxicity to reproduction.

Human experience

General:
Can be absorbed through the skin.

Human experience

Inhalation:
Respiratory tract: coughing, shortness of breath.

Human experience

Skin contact:
Skin: irritation, redness. (repeated or prolonged exposure)

Safety Data Sheet

LD2003 – PART B - RESIN

Revision date: 2015/11/12

Human experience

Eye contact:

Eye: Pain, redness, swelling, tearing.

12. Ecological Information

Chemical Fate and Pathway

Data on this material and/or its components are summarized below.

Data for 2-Propanol, 1-methoxy-, acetate (108-65-6)

Biodegradation:

Readily biodegradable. (10 d) biodegradation 83 %

Biological Oxygen Demand:

BOD = 0.363 mg/g

Octanol Water Partition Coefficient:

log Pow = 1.2 (measured)

Ecotoxicology

Data on this material and/or its components are summarized below.

Data for 2-Propanol, 1-methoxy-, acetate (108-65-6)

Aquatic toxicity data:

Practically nontoxic. *Oryzias latipes* (Orange-red killifish) 96 h LC50 > 100 mg/l

Practically nontoxic. *Oncorhynchus mykiss* (rainbow trout) 96 h LC50 = 134 mg/l

Practically nontoxic. *Pimephales promelas* (fathead minnow) 96 h LC50 = 161 mg/l

Aquatic invertebrates:

Practically nontoxic. *Daphnia magna* (Water flea) 48 h EC50 > 500 mg/l

Algae:

Practically nontoxic. *Selenastrum capricornutum* 72 h EC50 > 1,000 mg/l

Chronic toxicity to aquatic invertebrates:

Daphnia magna (Water flea) 21 d NOEC > 100 mg/l

13. Disposal Considerations

Dispose of in a licensed facility. Do not discharge into waterways or sewer systems without proper authorization.

Container disposal:

Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

14. Transport Information

Land transport

USDOT

Proper Shipping Name: Resin Solution

Hazard Class or Division: 3

UN/NA Number: 1866

Packaging Group: III

Hazard Label(s): Warning, Flammable Liquid

Hazard Placards(s): Flammable

Sea transport

IMDG

Proper Shipping Name: Resin Solution

Hazard Class or Division: 3

Safety Data Sheet

LD2003 – PART B - RESIN

Revision date: 2015/11/12

UN/NA Number: 1866
 Packaging Group: III
 Hazard Label(s): Warning, Flammable Liquid
 Hazard Placards(s): Flammable

Air transport

IATA/ICAO
 Proper Shipping Name: Resin Solution
 Hazard Class or Division: 3
 UN/NA Number: 1866
 Packaging Group: III
 Hazard Label(s): Warning, Flammable Liquid
 Hazard Placards(s): Flammable

15. Regulatory Information

EU. EINECS	EINECS	Does not conform
United States TSCA Inventory	TSCA	This product complies with TSCA Inventory requirements. The polymer component(s) is (are) eligible for the amended polymer exemption at 40 CFR Section 723.250.
Canadian Domestic Substances List (DSL)	DSL	This product contains one or several components that are not on the Canadian DSL nor NDSL lists.
China. Inventory of Existing Chemical Substances in China (IECSC)	IECSC (CN)	Does not conform
Japan. ENCS - Existing and New Chemical Substances Inventory	ENCS (JP)	Does not conform
Japan. ISHL - Inventory of Chemical Substances	ISHL (JP)	Does not conform
Korea. Korean Existing Chemicals Inventory (KECI)	KECI (KR)	Does not conform
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	PICCS (PH)	Does not conform
Australia Inventory of Chemical Substances (AICS)	AICS	Does not conform

United States – Federal Regulations

SARA Title III – Section 302 Extremely Hazardous Chemicals:

The components in this product are either not SARA Section 302 regulated or regulated but present in negligible concentrations.

SARA Title III - Section 311/312 Hazard Categories:

Fire Hazard, Chronic Health Hazard

SARA Title III – Section 313 Toxic Chemicals:

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) – Reportable Quantity (RQ):

The components in this product are either not CERCLA regulated, regulated but present in negligible concentrations, or regulated with no assigned reportable quantity.

United States – State Regulations

New Jersey Right to Know

No components are subject to the New Jersey Right to Know Act.

Pennsylvania Right to Know

Safety Data Sheet

LD2003 – PART B - RESIN

Revision date: 2015/11/12

Chemical Name	CAS-No.
saturated polyester resin solution	Proprietary
2-Propanol, 1-methoxy-, acetate	108-65-6

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive defects

16. Other Information

NFPA Hazard Codes:

Health : 2
Fire : 3
Reactivity : 1
Special : 0

SDS Prepared by:

Life Paint Company

The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication as part of Life Paint Company's Product Safety Program. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information obtained herein. Data sheets are available for all Life Paint products. You are urged to obtain data sheets for all Life Paint products you buy, process, use or distribute and you are encouraged and requested to advise those who may come in contact with such products of the information contained therein.

To determine applicability or effects of any law or regulation with respect to the product, user should consult his legal advisor or the appropriate government agency. Life Paint Company does not undertake to furnish advice on such matters.