



LIFE PAINT

PRODUCT SPECIFICATIONS

ARCHITECTURAL COATINGS

6470 Textured Primer

Description: An Acrylic Elastomeric Textured Primer.

Benefits:

- Primer and texture in one.
- Allows matching of surrounding textured surfaces for repairs.
- Part of our breathable coating systems.

Uses:

- * Concrete/Masonry Surfaces
- * Stucco/cinder block
- * Wood

Package Size: 5-gallon, 30-Gal Drum, 55-Gal Drum

Limitations:

Not intended for use as an exposed surface film. Refer to sales representative, place of purchase, or job specifications for top or finish coat.

Not recommended for application if rain is expected within 24 hours.

Surface Preparation:

Cleaning and General Preparation:

Surface preparation is extremely important for any paint product before it is used. Surface must be dry. Loose or peeling coatings must be removed by sand or water blasting with a minimum of 1500 psi. All loose or defective concrete or masonry and any surface contaminates such as dirt, oils, mildew, chalk and efflorescence which may adversely affect product adhesion and performance must be removed.

Mildew: DO NOT PAINT OVER MILDEW Mildew is a fungus, brown, black, grey or white in color which will rapidly grow through any coating applied over it. A solution of 50% household bleach and 50% water will kill the mildew. Rinse thoroughly. Read precautions on beach label before using.

Efflorescence: Efflorescence must be removed by sandblasting or thorough wire brushing and scraping followed by washing with a 10% solution of muriatic acid. Neutralize and rinse thoroughly.

Masonry: Surface must be free from dirt, dust, previous loose material, efflorescence, mildew, form oils, and release agents. Form oils and release agents must be sandblasted or wire brushed off.

Wood : Remove all loose material and dirt. Smoothly finished wood should be sanded first

Application: CAUTION: Do not apply when temperatures are below 50°F or expected to drop below 40°F within a 24 hour period or when heavy fog or rain is anticipated within 24 hours. Apply by brush, roller or spray.

Spray: Use tip size 1/4".

Coverage: Smooth 50-60 square feet
 Stucco 40-60 square feet
 Heavy Textured 40-50 square feet.

Thinning: DO NOT THIN.

Drying Time: Dries to touch in 30 minutes. Wait 24 hours before top coating.

Clean Up: Clean Tools and hands with warm soapy water and rinse thoroughly.

Storage: Transport and store in original, unopened, undamaged containers protected from freezing. If partially frozen, place in heated area and allow to warm. Do not apply heat directly to containers.

Maintenance: Life's 6470 Texture is not intended to be an exposed surface film. Refer to the topcoat technical bulletin for maintenance directions.

Safety, Health and Environmental Recommendations

Use appropriate personal protective equipment. Consult label or material safety data sheet which is available from Life Paint Corporation.

Technical Information

Type:	100% Acrylic Latex
Diluent:	Water
Solids Content:	62-64% by weight 58-60% by volume
Viscosity:	Mastic
Flash Point:	>200°F
Maximum V.O.C.:	50 grams per liter