

## AL-FLEX SYSTEM WEIGHT PER SQUARE FOOT

The figures below may vary slightly based on any variations in substrate and does not include flashing, drains or caulking.

PRODUCT CODE	DESCRIPTION	WEIGHT (PER SQ. FT.)	COVERAGE RATE
GML-PCS	2.5 Hot Dipped Galvanized Metal Lath	0.29 lbs.	@ 17.5 sq. ft. per sheet
LDS10	Galvanized Staples 1" wide crown 5/8" leg	0.03 lbs	@ 20 staples per sq. ft.
LD-1 + LD81	Proprietary Cement Blend (Base Coat)*	1.54 lbs.	@ 40 sq. ft. per batch
FM 50/100/500/2000	Fiberglass- 3/4 oz Chopped Strand	0.05 lbs.	@ 50 sq. ft./ 100 sq. ft./ 500 sq. ft. /2000 sq. ft. per sheet
1589	Flexible Waterproofing Resin	0.10 lbs	@ 40 sq. ft. per gallon
LD3	Proprietary Textured Cement	0.39 lbs.	@ 150 sq. ft. per batch
10 Series	100% Acrylic Pigmented Color Sealer	0.08 lbs	@ 125 sq. ft. per gallon
<b>TOTAL WEIGHT PER SQUARE FOOT (NOT INCLUDING FLASHING)</b>		<b>2.48 LBS</b>	

