# AL-FLEX SYSTEM
# WEIGHT PER SQUARE FOOT

The figures below may vary slightly based on any variations in substrate and does not include flashing, drains or caulking.

| PRODUCT CODE | DESCRIPTION | WEIGHT (PER SQ. FT.) | COVERAGE RATE |
|---|---|---|---|
| GML-PCS | 2.5 Hot Dipped Galvanized Metal Lath | 0.29 lbs | @ 17.5 sq. ft. per sheet |
| LDS10 | Galvanized Staples 1" wide crown 5/8" leg | 0.03 lbs | @ 20 staples per sq. ft. |
| LD-1 + LD81 | Proprietary Cement Blend (Base Coat)* | 1.54 lbs | @ 40 sq. ft. per batch |
| FM 50/100/500/2000 | Fiberglass- 3/4 oz Chopped Strand | 0.05 lbs | @ 50 sq. ft./ 100 sq. ft./ 500 sq. ft. 2000 sq. ft. per sheet |
| 1589 | Flexible Waterproofing Resin | 0.10 lbs | @ 40 sq. ft. per gallon |
| LD3 | Proprietary Textured Cement | 0.39 lbs | @ 150 sq. ft. per batch |
| 10 Series | 100% Acrylic Pigmented Color Sealer | 0.08 lbs | @ 125 sq. ft. per gallon |
| **TOTAL WEIGHT PER SQUARE FOOT (NOT INCLUDING FLASHING)** | | **2.48 LBS** | |